


# Ferrule Type, Fast-Acting Fuses

## For 13/32" x 1-1/2" (10.3mm x 38.1mm)

**KTQ**



### Dimensional Data



CATALOG SYMBOL: KTQ  
 FERRULE TYPE, FAST-ACTING  
 1-6A  
 600 VOLTS AC  
 UL RECOGNIZED, STD 248-14, (GUIDE # JDYX2,  
 FILE E19180)  
 BODY MATERIAL: MELAMINE  
 FERRULE MATERIAL: BRONZE  
 FERRULE PLATING: ALBALOY

- For control, gaseous vapor fixture, and HID ballast; electronic circuits.
- Fibre cartridge.
- Slightly more delay than type BBS to override transient currents.
- Mounts in Buss panel-mount fuseholders HPS-L, BM-series blocks, or 13/32" clips.

### Electrical Ratings (Catalog Symbol and Amperes)

#### 600 Volts AC


KTQ-1	KTQ-4
KTQ-1-6/10	KTQ-5
KTQ-2	KTQ-6
KTQ-3	

### Test Specifications

Load	Opening Time
110%	Indefinitely
135%	1 hr. (max.)

CE logo denotes compliance with European Union Low Voltage Directive (50-1000 VAC, 75-1500 VDC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 314-527-1270 for more information.

### Time-Current Characteristic Curves—Average Melt (Full Size Curves Available)



This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.