


Panel-Mount Fuseholder

For $1\frac{3}{32}$ " x $1\frac{5}{16}$ " to $1\frac{1}{2}$ " and
SC and Class CC Fuses

HPS Series



Dimensional Data



Catalog Symbol: HPS, HPS-EE, HPS-FF, HPS-JJ, and HPS-RR

Panel Mount

Agency Approvals: U.L. Recognized, Guide IZLT2, File E14853
CSA Certified: Class 6225-01, File 47235

Temperature Rating (RTI): 150°C

Electrical Ratings

Catalog Symbol	Amps	Volts AC	Fuse Description
HPS	30	600	$1\frac{1}{2}$ " (38.1mm).
HPS-C*,**	15	250	$1\frac{1}{2}$ " (38.1mm) clear knob.
HPS-L	5	600	BBS, $1\frac{3}{32}$ " x $1\frac{3}{8}$ " fuses.
HPS-EE	15	480	S.C. 0-15, $1\frac{3}{32}$ " x $1\frac{5}{16}$ " fuses.
HPS-JJ	20	480	S.C. 20, $1\frac{3}{32}$ " x $1\frac{3}{32}$ " fuses.
HPS-FF**	30	300	S.C. 25 & 30, $1\frac{3}{32}$ " x $1\frac{5}{8}$ " fuses.
HPS-RR**	30	600	KTK-R, LP-CC, FNQ-R Class CC fuses.
HPS-W*,**	30	600	$1\frac{3}{32}$ " x $1\frac{1}{2}$ " - Drip-proof knob.

* No U.L. Recognition

**No CSA Certification

General Information:

- Bayonet-type knob.
- For new designs see HPF series.
- Combination $\frac{1}{4}$ " quick-connect/solder terminals. (Standard solder type terminals available.)
- The -EE, -JJ, -FF, and -RR holders are U.L. Listed for branch circuit protection.

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000 Vac, 75-1500 Vdc). Refer to BIF document #8002 or contact Bussmann Application Engineering at 314-527-1270 for more information.

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.